



COMBINATION ROPES 6 STRAND WIRE ROPE CORE

NOMINAL ROPE DIAMETER	APPROXIMATE MASS	MINIMUM BREAKING FORCE	
		kN	kgf
mm	Kg/m		
8	0,09	14	1.440
10	0,15	23	2.350
12	0,21	33	3.340
14	0,29	47	4.570
16	0,41	65	6.640
18	0,50	79	8.100
20	0,59	94	9.570
22	0,79	126	12.800
24	0,92	146	14.900
26	1,14	183	18.600
28	1,29	206	21.000
30	1,50	239	24.400
32	1,73	277	28.300
34	1,92	308	31.400
36	2,20	352	35.900
38	2,50	401	40.900
40	2,76	443	45.100

- FC AND IWRC
- A FLEXIBLE ROPE WITH VARIOUS APPLICATIONS SUCH AS IN FISHING, INDUSTRY, PLAYGROUNDS
- FISHING - SELVEDGE ROPE, HEADLINE, FRAME LINES
- GOOD ABRASION, LONG LIFETIME, EASY HANDLING



6x7 FIBER CORE

NOMINAL ROPE DIAMETER	APPROXIMATE MASS	MINIMUM BREAKING FORCE 1570 N/mm ²	
		kN	kgf
mm	Kg/m		
8	0,22	34	3.500
9	0,27	43	4.400
10	0,34	53	5.400
11	0,40	63	6.400
12	0,48	76	7.700
13	0,56	88	9.000
14	0,67	106	10.800
16	0,87	137	14.000
18	1,10	172	17.500
20	1,34	210	21.400
22	1,66	261	26.600

- ROPE TO BE USED IN SMALL TRAWLERS AND DOUBLE / TRIPLE RIGGED VESSELS (SHRIMPERS)
- THICK OUTER WIRES WITH GOOD LIFETIME
- HIGH STRENGTH ROPE



SEINE 22

NOMINAL ROPE DIAMETER	APPROXIMATE MASS	MINIMUM BREAKING FORCE 1770 N/mm ²	
		kN	kgf
mm	Kg/m		
14	0,60	92	9.300
16	0,81	123	12.600
18	1,06	160	16.300
19	1,16	175	17.900
20	1,33	201	20.500
22	1,51	229	23.300
24	1,83	278	28.300
25	2,05	310	31.600
26	2,18	331	33.800

- FLEXIBLE PURSE WIRE, VERY POPULAR ON SMALL AND MEDIUM PURSE SEINERS
- THICKER OUTERWIRES, COMPARED TO 6x24s + 7cr
- VERY EASY TO HANDLE AND SPLICE
- DUAL TENSILE STRENGTH - HIGHER MBL
- GOOD RESISTANCE AGAINST CRUSHING
- REDUCED WEAR ON SHEAVES AND GUIDING GEAR AND PURSE SEINE RINGS
- NO CONTACT BETWEEN THE WIRES IN THE STRANDS